




ПРЕСС-СИСТЕМЫ ТРУБОПРОВОДОВ ИЗ НЕРЖАВЕЮЩЕЙ СТАЛИ

- РАЗМЕРЫ: DN15—DN54
- РАБОЧЕЕ ДАВЛЕНИЕ: PN16
- ТЕМПЕРАТУРА РАБОЧЕЙ СРЕДЫ: +110 °C
- УПЛОТНЕНИЕ: EPDM
- УПАКОВКА: DIY
- МАТЕРИАЛ: НЖ. СТАЛЬ SS304
- ГАРАНТИЯ: 2 ГОДА





ТРУБА В ШТАНГАХ

d	D	S	L
18	18±0.1	1.2±0.1	2000±2
22	22±0.12	1.2±0.12	2000±2
28	28±0.12	1.5±0.12	2000±2
35	35±0.15	1.5±0.15	2000±2
42	42±0.15	1.5±0.15	2000±2
54	54±0.15	1.5±0.15	2000±2

МУФТА РАВНОПРОХОДНАЯ

d	L	L ₁	D
15	23±1	63±2	18.5±0.2
18	23±1	63±2	21.5±0.2
22	26±1	67±2	25.5±0.2
28	30±1	74±2	31.5±0.2
35	28±2	71±2	38.7±0.4
42	36±2	91±2	45.8±0.4
54	40±2	95±2	57.8±0.4

УДЛИНИТЕЛЬ

d	L	D
15	80±2	18.5±0.2
18	81±2	21.5±0.2
22	85±2	25.5±0.2
28	95±2	31.5±0.2
35	107±2	38.7±0.4
42	123±2	45.8±0.4
54	135±2	57.8±0.4

ПЕРЕХОД


d	L	L ₁	D
18-15	23±1	64±2	18.5±0.2
22-15	23±1	70±2	18.5±0.2
22-18	23±1	70±2	18.5±0.2
28-15	23±1	73±2	21.5±0.2
28-22	26±1	74±2	25.5±0.2
35-28	30±1	77±2	31.5±0.2
42-35	28±2	88±2	38.7±0.4
54-42	36±2	70±4	45.8±0.4

УГОЛЬНИК 90°

d	D	L	L ₁
15	18.5±0.2	23±1	47±2
18	21.5±0.2	23±1	55±2
22	25.5±0.2	26±1	60±2
28	31.5±0.2	30±1	69±2
35	38.7±0.4	28±2	80±2
42	45.8±0.4	36±2	91±2
54	57.8±0.4	40±2	115±2


УГОЛЬНИК 90° ОДНОРАСТРУБНЫЙ

d	L	L ₁	L ₂	D
15	23±1	48±2	47±2	18.5±0.2
18	23±1	59±2	50±2	21.5±0.2
22	26±1	61±2	55±2	25.5±0.2
28	30±1	74±2	65±2	31.5±0.2
35	28±2	92±2	76±2	38.7±0.4
42	36±2	115±2	93±2	45.8±0.4
54	40±2	133±2	115±2	57.8±0.4




УГОЛЬНИК 45°

d	L	L ₁	D
15	23±1	34±2	18.5±0.2
18	23±1	40±2	21.5±0.2
22	26±1	43±2	25.5±0.2
28	30±1	48±2	31.5±0.2
35	28±2	54±2	38.7±0.4
42	36±2	63±2	45.8±0.4
54	40±2	73±2	57.8±0.4




УГОЛЬНИК 45° ОДНОРАСТРУБНЫЙ

d	L	L ₁	D
15	23±1	34±2	18.5±0.2
18	23±1	34±2	21.5±0.2
22	26±1	36±2	25.5±0.2
28	30±1	40±2	31.5±0.2
35	28±2	46±2	38.7±0.4
42	36±2	60±2	45.8±0.4
54	40±2	67±2	57.8±0.4




УГОЛЬНИК 90° ПЕРЕХОДНИК НР

d-R	L	L ₁	L ₂	D
15-1/2	23±1	51±2	48±2	18.5±0.2
18-1/2	23±1	47±2	55±2	21.5±0.2
22-1/2	26±1	52±2	60±2	25.5±0.2
22-3/4	26±1	55±2	60±2	25.5±0.2




УГОЛЬНИК 90° ПЕРЕХОДНИК ВР

d-Rp	L	L ₁	L ₂	D
15-1/2	23±1	24±2	52±2	18.5±0.2
18-1/2	23±1	24±2	52±2	21.5±0.2
18-3/4	23±1	28±2	56±2	21.5±0.2
22-1/2	26±1	24±2	54±2	25.5±0.2
22-3/4	26±1	28±2	58±2	25.5±0.2




ПЕРЕХОДНИК ВР

d-R	D	L	H
15-1/2	18.5±0.2	23±1	54±2
18-1/2	21.5±0.2	21.5±0.2	21.5±0.2
18-3/4	21.5±0.2	21.5±0.2	21.5±0.2
22-1/2	25.5±0.2	25.5±0.2	25.5±0.2
22-3/4	25.5±0.2	25.5±0.2	25.5±0.2
28-3/4	31.5±0.2	31.5±0.2	31.5±0.2
28-1	31.5±0.2	31.5±0.2	31.5±0.2
35-1	38.7±0.4	38.7±0.4	38.7±0.4
35-1/4	38.7±0.4	38.7±0.4	38.7±0.4
42-1/2	45.8±0.4	45.8±0.4	45.8±0.4
54-2	57.8±0.4	57.8±0.4	57.8±0.4




ПЕРЕХОДНИК НР

d-R	L	H	D	d
15-1/2	23±1	56±2	18.5±0.2	20±1
15-3/4	23±1	59±2	18.5±0.2	25±1
18-1/2	23±1	56±2	21.5±0.2	20±1
18-3/4	23±1	59±2	21.5±0.2	25±1
22-1/2	26±1	58±2	25.5±0.2	20±1
22-3/4	26±1	61±2	25.5±0.2	25±1
22-1	26±1	64±2	25.5±0.2	32±1
28-3/4	30±1	65±2	31.5±0.2	25±1
28-1	30±1	68±2	31.5±0.2	32±1
35-1	28±2	66±2	38.7±0.4	32±1
35-1/4	28±2	71±2	38.7±0.4	40±1
42-1/2	36±2	81±2	45.8±0.4	46±2




ПЕРЕХОДНИК С НАКИДНОЙ ГАЙКОЙ ВР

d-Rp	L	H	D
15-1/2	23±1	59±2	18.5±0.2
15-3/4	23±1	69±2	18.5±0.2
18-1/2	23±1	58±2	21.5±0.2
18-3/4	23±1	60±2	21.5±0.2
22-1/2	26±1	69±2	25.5±0.2
22-3/4	26±1	64±2	25.5±0.2
28-3/4	30±1	75±2	31.5±0.2
28-1	30±1	70±2	31.5±0.2
35-1	28±2	77±2	38.7±0.4
35-1/4	28±2	68±2	38.7±0.4
42-1/2	36±2	82±2	45.8±0.4
54-2	40±2	85±2	57.8±0.4




УГОЛЬНИК НАСТЕННЫЙ 90° ВР С КРЕПЛЕНИЕМ

d-R	D	L	L ₁	L ₂
15-1/2	18.5±0.2	23±1	24±2	52±2
18-1/2	21.5±0.2	23±1	24±2	52±2
22-3/4	25.5±0.2	26±1	24±2	54±2
22-3/4	25.5±0.2	26±1	28±2	58±2




ТРОЙНИК РАВНОПРОХОДНОЙ

d	L	L ₁	L ₂	D
15	23±1	77±2	39±2	18.5±0.2
18	23±1	80±2	40±2	21.5±0.2
22	26±1	86±2	45±2	25.5±0.2
28	30±1	106±2	51±2	31.5±0.2
35	28±2	110±3	54±3	38.7±0.4
42	36±2	137±3	66±3	45.8±0.4
54	40±2	157±3	76±3	57.8±0.4




ТРОЙНИК ПЕРЕХОДНОЙ

d-d1-d	L	L ₁	L ₂	H	D	d
18-15-18	23±1	23±1	40±2	80±2	21.5±0.2	18.5±0.2
22-15-22	26±1	23±1	43±2	86±2	25.5±0.2	18.5±0.2
22-18-22	26±1	23±1	43±2	86±2	25.5±0.2	21.5±0.2
28-15-28	30±1	23±1	46±2	106±2	31.5±0.2	18.5±0.2
28-22-28	30±1	26±1	48±2	106±2	31.5±0.2	25.5±0.2
35-15-35	28±2	23±1	49±2	110±3	38.7±0.4	18.5±0.2
35-22-35	28±2	26±1	52±2	110±3	38.7±0.4	25.5±0.2
35-28-35	28±2	30±1	55±2	110±3	38.7±0.4	31.5±0.2
42-35-42	36±2	28±2	57±2	137±3	45.8±0.4	38.7±0.4
54-42-54	40±2	36±2	72±2	157±3	57.8±0.4	45.8±0.4




ТРОЙНИК ПЕРЕХОДНИК ВР

d-Rp	L	L ₁	L ₂	D
15-1/2-15	23±1	77±2	34±2	18.5±0.2
18-1/2-18	23±1	80±2	34±2	21.5±0.2
18-3/4-18	23±1	80±2	34±2	21.5±0.2
22-1/2-22	26±1	86±2	37±2	25.5±0.2
22-3/4-22	26±1	86±2	37±2	25.5±0.2
28-1/2-28	30±1	106±2	40±2	31.5±0.2
28-3/4-28	30±1	106±2	40±2	31.5±0.2
28-1-28	30±1	106±2	45±2	31.5±0.2
35-1/2-35	28±2	110±3	43±2	38.7±0.4
35-1-35	28±2	110±3	48±2	38.7±0.4
35-1/4-35	28±2	110±3	51±2	38.7±0.4
42-1/2-42	36±2	137±3	47±2	45.8±0.4
42-1-42	36±2	137±3	52±2	45.8±0.4
42-1/4-42	36±2	137±3	55±2	45.8±0.4
54-1/2-54	40±2	157±3	53±2	57.8±0.4
54-1-54	40±2	157±3	58±2	57.8±0.4




ТРОЙНИК-ПЕРЕХОДНИК НР

Size	L	L ₁	L ₂	D
15-1/2-15	23±1	77±2	36±2	18.5±0.2
18-1/2-18	23±1	80±2	36±2	21.5±0.2
18-3/4-18	23±1	80±2	39±2	21.5±0.2
22-1/2-22	26±1	86±2	39±2	25.5±0.2
22-3/4-22	26±1	86±2	42±2	25.5±0.2
28-1/2-28	30±1	106±2	41±2	31.5±0.2
28-3/4-28	30±1	106±2	44±2	31.5±0.2
28-1-28	30±1	106±2	47±2	31.5±0.2
35-1-35	28±2	110±3	51±2	38.7±0.4
35-1/4-35	28±2	110±3	56±2	38.7±0.4
42-1-42	36±2	137±3	55±2	45.8±0.4
42-1/4-42	36±2	137±3	60±2	45.8±0.4
54-1-54	40±2	157±3	61±2	57.8±0.4
54-1/4-54	40±2	157±3	66±2	57.8±0.4



ЗАГЛУШКА

d	L	D
15	36±2	18.5±0.2
18	38±2	21.5±0.2
22	39±2	25.5±0.2
28	45±2	31.5±0.2
35	42±2	38.7±0.4
42	51±2	45.8±0.4
54	54±2	57.8±0.4



КОЛЕНО ОБВОДНОЕ

d	L	L ₁
15	195±2	24±2
18	199±2	25±2
22	239±2	28±2
28	268±2	33±2